

PRODUCT INFORMATION



AGS 221 Gel

Art. No: 3625

For smooth factory made/painted surfaces



AGS 221 GEL is a graffiti and paint remover. For use on exterior and interior surfaces. AGS 221 is used mainly on smooth factory made/painted surfaces. Can also be used on porous substrates. Readily biodegradable according to OECD 302 B.

INSTRUCTIONS FOR USE

AGS 221 GEL is used for graffiti and paint removal from smooth factory made/painted surfaces, for example trains, coaches & buses, cars and industrial buildings etc. Can also be used on porous substrates.

Graffiti-removal from smooth surfaces:

Apply a thick layer of **AGS 221 GEL** with a brush. Cover all graffiti and wait 3-5 minutes. Agitate the whole area with a brush. When graffiti has dissolved, Jet off with medium-pressure and preferably warm water. If required, repeat the process.

Graffiti-removal from porous surfaces:

Apply **AGS 221 GEL** with airless sprayer or brush. Agitate the whole area with a brush. Leave area to dissolve all graffiti approximately ½ - 4 hours. Jet off with hot water and high pressure, (90°C, 150 bar/2175 PSI). Lance nozzle spread should be 15 - 25 degrees and water flow should be 15 to 20 ltrs/minute, (4-5 gal/minute).

Note!

For metal surfaces do not use too much pressure, as the effect can be negative. Instead, wipe with a sponge or cloth and rinse with warm water.

Dosage

Use concentrate.

Consumption

0,3 - 1,0 litre/m².

Guidelines

- Viscous yellowish fluid. The colour may vary.
- Supplied in 5 litres plastic Jerricans or 20 litres plastic bucket.
- Specific weight 1.05 kg/litre.
- Faint solvent odour.
- Flash point 97°C.
- Contains gamma-Butyrolacton, 2-Butoxyethanol, triethanolamine.

Precautions

Gloves. Safety glasses in case of splashes.

Marking

AGS 221 GEL is Not classified as dangerous.
Not classified in ADR or IMDG.

Storage

Store at room temperature in original closed container.

Shelf life

Approximately 24 months in un opened container.

Modified: 2007-12-21

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and be responsible for the result.

TRION TENSID AB

Svederusgatan 1-3 | SE-754 50 UPPSALA | SWEDEN Tel: +46 18-15 61 90 Fax: +46 18-69 66 27
Email: info@trion.se Web: www.trion.se